




KMB16S

Single Phase 1.0 AMP Surface Mount Schottky Bridge Rectifier

Features

- Schottky Brrier Chip
- Low Power Loss,High Efficiency
- Ideally Suited for Automatic Assembly
- Surge Overload Rating to 30A Peak
- Plastic Case Material has UL Flammability Classification Rating 94V-0

Case: MBS



dimensions in inches and (millimeters)

Mechanical Data

- Case: MB-S, molded plastic
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number
- Lead Free: For RoHS / Lead Free Version,

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase,half wave,60Hz,resistive or inductive load

For capacitive load derate current by 20%

Type Number	SYMBOL	KMB16S	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	60	V
Maximum RMS Voltage	V_{RMS}	42	V
Maximum DC Blocking Voltage	V_{DC}	60	V
Average Rectified Output Current @ $T_c=100^{\circ}C$	$I_{F(AV)}$	1.0	A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30	A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t	3.735	A ² s
Forward Voltage @ $I_F=1.0A$	V_{FM}	0.7	V
Peak Reverse Current @ $T_J=25^{\circ}C$	I_R	0.1	mA
At Rated DC Blocking Voltage @ $T_J=100^{\circ}C$		10	
Typical Junction Capacitance (Note 1)	C_J	68	pF
Typical Thermal Resistance	$R_{\theta JA}$	95	$^{\circ}C/W$
	$R_{\theta JC}$	15	
Operating Temperature Range	T_J	-55 to+150	$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}C$

Note:

1. Measured at 1.0 MHz and Applied reverse Voltage of 4.0V D.C



KMB16S

Single Phase 1.0 AMP Surface Mount Schottky Bridge Rectifier

Fig. 1 Forward Current Derating Curve




Fig. 2 Typ. Forward Characteristics




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Reverse Characteristics





Fig.5 Mounting PAD Layout





Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from XINNUO
- XINNUO reserves the right to make changes to this document and its products and specifications
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.

XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.