


**Features**

- Small package
- High Conductance

SOT-23**Mechanical Data**

- Case: Molded Plastic, SOT-23
- Epoxy: UL 94V-0 rate flame retardant
- Terminals: Plated Leads Solderable per MIL-STD-750, Method-2026.
- Marking: JF
- Mounting Position : Any.
- Equivalent Circuit:



Dimensions in inches and (millimeters)

Maximum Ratings Maximum Ratings (Rating at 25°C ambient temperature unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Reverse Voltage	V_{RRM}	75	V
Working Peak Reverse Voltage	V_{RWM}		
DC Blocking Voltage	V_R		
Forward Continuous Current (Note 1)	I_F	300	mA
Average Rectified Output Current (Note 1)	I_O	150	mA
Peak Forward Surge Current (Note 1) @ $t < 1.0\mu s$	I_{FSM}	2.0	A
Power Dissipation (Note 1)	P_d	350	mW
Typical Thermal Resistance, Junction to Ambient Air (Note 1)	$R_{\theta JA}$	357	K/W
Operating and Storage Temperature Range	T_j, T_{STG}	-65 to +150	°C

Electrical Characteristics (Rating at 25°C ambient temperature unless otherwise specified.)

Characteristic	Symbol	Min	Max	Unit	Test Condition
Forward Voltage	V_F	—	0.855 1.0	V	@ $I_F = 10mA$ @ $I_F = 50mA$
Reverse Leakage Current	I_R	—	2.5	μA	@ $V_R = 75V$
Junction Capacitance	C_j	—	2.0	pF	$V_R = 0V, f=1.0MHz$
Reverse Recovery Time	t_{rr}	—	6.0	nS	$I_F = I_R = 10mA$, $I_{RR} = 0.1 \times I_R, R_L = 100$



Rating And Characteristic Curves




Fig. 1 Power Derating Curve




Fig. 2 Forward Characteristics




Fig. 3 Typical Reverse Characteristics




Fig. 4 Typical Capacitance vs. Reverse Voltage



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.