




1. Features

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance

SOT-23-3L



2. Mechanical Data

- Case:Molded Plastic,SOT-23-3L.
- Epoxy:UL 94V-0 rate flame retardant.
- Terminals:Plated Leads Solderable per MIL-STD-750, Method-2026.
- Marking:marked on body.



BAS21-3L

Marking: JS



BAS21A-3L

Marking:JS2



BAS21C-3L

Marking:JS3



BAS21S-3L

Marking: JS4

3. Maximum Ratings

Electrical Characteristics Rating at 25°C ambient temperature unless otherwise specified.

Characteristic	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	250	V
Working Peak reverse voltage	V_{RWM}	250	V
Reverse Voltage	V_R	250	V
Continuous Forward Current	I_F	400	mA
Average Rectified Output Current	I_O	200	mA
Repetitive Peak Forward Current	I_{FRM}	625	mA
Non-Repetitive Peak Forward Current	I_{FSM}	2.5	A
$t = 1 \mu s$		0.5	
$t = 1 s$			
Power Dissipation	P_D	225	mW
Thermal Resistance. Junction to Ambient Air	$R_{\theta JA}$	556	°C/W
Junction Temperature	T_J	-65 to+150	°C
Storage Temperature Range	T_{stg}	-65 to+150	°C

4. Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameters	Symbol	Cindition	Min	TYP	Max	Unit
Reverse breakdown voltage	$V_{(BR)}$	$I_F = 100\mu A$	250	-	-	V
Forward Voltage	V_F	$I_F = 100mA$ $I_F = 200mA$	-	-	1000 1250	mV
Reverse Current	I_R	$V_R = 200V$	-	-	1	μA
Diode Capacitance	C_D	$V_R = 0 V, f = 1 MHz$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=10mA, I_{rr}=0.1*I_R,$ $R_L=100\Omega$	-	-	50	ns



5. Rating And Characteristic Curves

Fig.1 Forward current of forward voltage.






Fig.2 Leakage current of junction temperature.






6. Soldering Parameters




Reflow Condition		Lead-free
Pre Heat	Temp. min(T_s (min))	150℃
	Temp. max(T_s (min))	200℃
	Time(min to max)(t_s)	60~120s
Aver. ramp up rate(Liquidus Temp.)(T_L)to peak		3℃/s max
T_s (max) to T_L -Ramp-up Rate		3℃/s max
Reflow	Temp.(T_L)(Liquidus)	217℃
	Temp.(t_L)(Liquidus)	60~150s
Peak Temp.(T_P)		260 ^{+0/-5} ℃
Time within actual peak Temp.(t_p)		30s max
Ramp-down Rate		6℃/s max
Time 25℃ to peak Tempe.(T_p)		8 minutes max
Do not exceed		260℃

7. Dimensions




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A2	0.041	0.047	1.050	1.200
A1	0.000	0.004	0.010	0.100
b	0.014	0.020	0.350	0.500
c	0.004	0.006	0.090	0.150
D	0.110	0.118	2.800	3.000
E	0.059	0.067	1.500	1.700
E1	0.102	0.118	2.600	3.000
e1	0.071	0.079	1.800	2.000
L1	0.010	0.022	0.250	0.550

Mounting PAD Layout



8. Part Marking System



9. Package Information

Package	Part Number	Marking Code	Tape Width(mm)	Quantity(pcs)
SOT-23-3L	BAS21-3L	JS	8	3000
SOT-23-3L	BAS21A-3L	JS2	8	3000
SOT-23-3L	BAS21C-3L	JS3	8	3000
SOT-23-3L	BAS21S-3L	JS4	8	3000



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.