




### Features

- Guard ring protection
- Low forward voltage drop
- For use in low voltage, high frequency inverters
- High surge current capability

### SOD-323



### Mechanical Data

- Case:Molded Plastic,SOD-323
- Epoxy:UL 94V-0 rate flame retardant
- Terminals:Plated Leads Solderable per MIL-STD-750,Method-2026
- Mounting Position : Any.
- Marking: SM

Dimensions in inches and (millimeters)

### Maximum Ratings Maximum Ratings (Rating at 25°C ambient temperature unless otherwise specified.)





Symbol	Parameter	Value	Unit
$V_{RRM}$	Maximum recurrent peak reverse voltage	60	V
$V_{RMS}$	Maximum RMS voltage	42	
$V_{DC}$	Maximum DC blocking voltage	60	
$I_F$	Continuous forward current	1	A
$I_{FSM}$	Non-repetitive Peak forward surge current@t=8.3ms	10	
$P_{tot}$	Total power dissipation	250	mW
$R_{\theta JA}$	Thermal resistance junction to ambient air	400	°C/W
$T_J$	Junction temperature	125	°C
$T_{stg}$	storage temperature	-55~+150	°C

### Electrical Characteristics (Rating at 25°C ambient temperature unless otherwise specified.)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Maximum instantaneous forward voltage	$V_F$	$I_F=1A$			0.7	V
Maximum DC reverse current at rated DC blocking voltage	$I_R$	$V_R=60V$			0.1	mA
Total capacitance	$C_{tot}$	$V_R=4V, f=1MHz$			120	pF



Rating And Characteristic Curves





## Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.