




1. Features

- Low collector-to-emitter saturation voltage.
- Fast switching speed.
- Large current capacity and wide ASO.
- We declare that the material of product compliance with RoHS requirements and Halogen Free.

SOT-89



1.BASE
2.COLLECTOR
3.EMITTER

2. Mechanical Data

- Case:Molded Plastic,SOT-89 .
- Epoxy:UL 94V-0 rate flame retardant.
- Terminals:Plated Leads Solderable per MIL-STD-750,Method-2026.
- Marking:G
- Mounting Position : Any.

3. Maximum Ratings

Electrical Characteristics Rating at 25°C ambient temperature unless otherwise specified.

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	50	V
Emitter-Base Voltage	V_{EBO}	6	V
Collector Current	I_C	2	A
Collector Current(Pulse)	I_{CP}	4	A
Collector Power Dissipation	P_C	0.5	W
Junction Temperature	T_j	-55~+150	°C
Storage Temperature	T_{stg}	-55~+150	°C

4. Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Characteristics	Symbol	Condition	Min	TYP	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	50	-	-	V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1\text{mA}, I_B=0$	50	-	-	V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100\mu\text{A}, I_C=0$	6	-	-	V
Collector cut-off current	I_{CBO}	$V_{CB}=50\text{V}, I_E=0$	-	-	1	uA
Emitter cut-off current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$	-	-	1	uA
DC current gain	h_{FE}	$V_{CE}=2\text{V}, I_C=-50\text{mA}$	180	-	450	-
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=700\text{mA}, I_B=35\text{mA}$	-	0.13	0.35	V
Base -emitter saturation voltage	$V_{BE(sat)}$	$I_C=700\text{mA}, I_B=35\text{mA}$	-	-	1.1	V
Transition frequency	f_T	$V_{CE}=10\text{V}, I_E=300\text{mA}, f=300\text{MHz}$	-	360	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$	-	12	-	pF



5. Rating And Characteristic Curves

Fig.1 Static Characteristic




Fig.2 DC current Gain




Fig.3 Collector-Emitter Saturation Voltage




Fig.4 Base-Emitter Saturation Voltage




Fig.5 Base-Emitter on Voltage






Fig.6 Output Capacitance






6. Soldering Parameters




Reflow Condition		Lead-free
Pre Heat	Temp. min(T_s (min))	150℃
	Temp. max(T_s (min))	200℃
	Time(min to max)(t_s)	60~120s
Aver. ramp up rate(Liquidus Temp.)(T_L)to peak		3℃/s max
T_s (max) to T_L -Ramp-up Rate		3℃/s max
Reflow	Temp.(T_L)(Liquidus)	217℃
	Temp.(t_L)(Liquidus)	60~150s
Peak Temp.(T_P)		260 ^{+0/-5} ℃
Time within actual peak Temp.(t_p)		30s max
Ramp-down Rate		6℃/s max
Time 25℃ to peak Tempe.(T_p)		8 minutes max
Do not exceed		260℃

7. Dimensions




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.169	0.185	4.300	4.700
B	0.055	0.071	1.400	1.800
C	0.154	0.167	3.900	4.250
D	0.035	0.047	0.900	1.200
E	0.091	0.106	2.300	2.700
F	0.118		3.000	
G	0.013	0.024	0.320	0.600
H	0.013	0.024	0.320	0.600
J	0.013	0.020	0.340	0.500
K	0.055	0.063	1.400	1.600
L	0.059		1.500	
X	0.031		0.800	
Y	0.047		1.200	
X1	0.031		0.800	
Y1	0.087		2.200	
X2	0.079		2.000	
Y2	0.098		2.500	
C	0.059		1.500	

Mounting PAD Layout



8. Part Marking System



9. Package Information

Package	Part Number	Marking Code	Quantity(pcs)
SOT-89	PBSS4250X	G	1000



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.