




1.Features

- High speed Switching
- Suitable for Switching Regulator or Electronic Transformer For Halogen Lamps

Case:TO-220



2.Mechanical Data

- Case:Molded Plastic,TO-220
- Epoxy:UL 94V-0 rate flame retardant
- Terminals:Plated Leads Solderable per MIL-STD-750,Method-2026.
- Marking: marked on body.
- Mounting Position : Any.

3.Maximum Ratings and Electrical Characteristics

Rating at 25°C Ambient temperature unless otherwise specified

Parameters	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	700	V
Collector-Emitter Voltage	V_{CEO}	400	V
Emitter-Base Voltage	V_{EBO}	9	V
Collector Current -Continuous	I_C	4	A
Power Dissipation $T_A=25^\circ\text{C}$	P_C	80	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Operating and Storage Temperature Range	T_{stg}	-55 to +150	$^\circ\text{C}$

4.Electrical Characteristics (TA=25°C unless otherwise noted)

Parameters	Symbol	Cindition	Min	TYP	Max	Unit
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}, I_B = 0$	400	-	-	V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	9	-	-	V
Collector cut-off current	I_{CBO}	$V_{CB} = 700\text{V}, I_E = 0$	-	-	100	mA
Emitter cut-off current	I_{EBO}	$V_{EB} = 450\text{V}, I_B = 0$	-	-	250	mA
*DC current gain	h_{FE}	$V_{CE} = 5\text{V}, I_C = 10\text{mA}$	8	-	40	-
		$V_{CE} = 5\text{V}, I_C = 0.5\text{A}$	10			
		$V_{CE} = 5\text{V}, I_C = 0.5\text{A}$	8			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 1\text{A}, I_B = 0.2\text{A}$	-	-	0.5	V
		$I_C = 2\text{A}, I_B = 0.5\text{A}$			0.7	
		$I_C = 4\text{A}, I_B = 1\text{A}$			1.1	
*Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = 1\text{A}, I_B = 0.25\text{A}$	-	-	1.1	V
		$I_C = 2\text{A}, I_B = 0.4\text{A}$			1.2	
Transition frequency	f_T	$V_{CE} = 10\text{V}, I_B = 0.1\text{A}$	4	-	-	MHz
Turn On Time	t_{ON}	$V_{CC} = 150\text{V}, I_C = 2.5\text{A}$ $I_{B1} = 0.5\text{A}, I_{B2} = -0.5\text{A},$ $t_p = 30\text{ms}$	-	-	0.8	μs
Storage Time	t_{STG}				4	μs
Fall Time	t_f				0.9	μs

• Pulsed: Pulse duration = 300 μs , duty cycle 1.5 %



5. Rating And Characteristic Curves

Fig.1 DC current Gain




Fig.2 Base-Emitter/Collector-Emitter Saturation Voltage




Fig.3 Collector Output Capacitance




Fig.4 Turn On Time




Fig.5 Turn Off Time






Fig.6 Safe Operating Area







6.Dimensions



Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.169	0.184	4.30	4.67
A1	0.098	0.111	2.50	2.82
b	0.028	0.036	0.70	0.91
b1	0.046	0.055	1.17	1.40
c	0.012	0.024	0.30	0.60
c1	0.045	0.055	1.15	1.40
D	0.390	0.402	9.90	10.20
E	0.335	0.354	8.50	9.00
E1	0.472	0.492	12.00	12.50
e	0.094	0.104	2.40	2.64
F	0.102	0.110	2.60	2.80
L	0.520	0.543	13.20	13.80
L1	0.150	0.165	3.80	4.20
Φ	0.139	0.163	3.54	4.14

7. Part Marking System



8. Package Information

Package	Packing Type	Quantity(pcs)
TO-220	Tube	50



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.