




1. Features

- Output Current up to 1 A
- Low Dropout Voltage (1.2V at 1A Output Current)
- Three Terminal Adjustable(ADJ)
- Line Regulation typically at 0.1% max
- Load Regulation typically at 0.2% max
- Internal Current and Terminal Protection
- Maximum Input Voltage - 15V
- 100% Thermal Limit Burn-In

2. Mechanical Data

- Case:Molded Plastic,SOT-223 .
- Epoxy:UL 94V-0 rate flame retardant.
- Terminals:Plated Leads Solderable per MIL-STD-750,Method-2026.
- Marking:1117-ADJ
- Mounting Position : Any.

SOT-223



1 ADJ

2 OUT

3 IN

4 OUT

3. Maximum Ratings

Electrical Characteristics Rating at 25°C ambient temperature unless otherwise specified.

Characteristic	Symbol	Value	Unit
Power Dissipation	P_D	Internally Limited	W
Input Voltage	V_{IN}	15	V
Voltage Difference	$V_{IN} - V_{OUT}$	10	V
Junction Temperature	T_j	-40~+125	°C
Storage Temperature	T_{stg}	-65~+150	°C
Lead Temperature (Soldering, 10 sec)	T_{LEAD}	300	°C
Minimum ESD Rating (HBM)	V_{ESD}	2	KV

4. Electrical Characteristics (Refer to the test circuits, $T_J=25^{\circ}\text{C}$ $C_O=10\mu\text{F}$ unless otherwise specified)

Characteristics	Symbol	Condition	Min	TYP	Max	Unit
Output Voltage(Note 1)	V_O	$I_O=10\text{mA}$	1.238	1.25	1.265	V
		$I_O=10\text{mA}-1\text{A}, V_{IN}-V_O=1.5-3.75\text{V}$	1.219	-	1.281	V
Line Regulation (Note 1)	ΔV_O	$I_O=10\text{mA}, V_{IN}-V_O=1.5-3.75\text{V}$	-	-	0.20%	-
		$I_O=10\text{mA}-1\text{A}, V_{IN}-V_O=2\text{V}$	-	-	0.40%	-
Operating Input Voltage	V_{IN}		-	-	15	V
Adjustment Pin Current	I_{ADJ}	$V_{IN}-V_O=1.5-12\text{V}, I_O=100\text{mA}$	-	-	120	μA
Adjustment Pin Current Change	ΔI_{ADJ}	$V_{IN}-V_O=1.5-12\text{V}, I_O=10\text{mA}-1\text{A}$	-	-	5	μA
Quiescent Current	I_Q	$V_{IN} - V_O = 5\text{V}$	-	-	10	mA
Current Limit	I_O		1000	-	-	mA
Supply Voltage Rejection	SVR	$I_O=40\text{mA}, f=12\text{Hz}, T_J=25^{\circ}\text{C}, V_{IN}-V_O=3\text{V}, V_{NIPPLE}=1V_{PP}$	60	-	-	dB
Dropout Voltage	V_D	$I_O = 100\text{mA}$	-	-	1.1	V
		$I_O = 500\text{mA}$	-	-	1.2	V
		$I_O = 1000\text{mA}$	-	-	1.3	V

Note1 : Low duty pulse testing with Kelvin connections required.

Note2 : 120Hz input ripple

Note3 : $\Delta V_{OUT} = 1\%$



5. Rating And Characteristic Curves

Fig.1 Typical Application






Fig.2 Typical Application






6. Soldering Parameters




Reflow Condition		Lead-free
Pre Heat	Temp. min(T_s (min))	150°C
	Temp. max(T_s (min))	200°C
	Time(min to max)(t_s)	60~120s
Aver. ramp up rate(Liquidus Temp.)(T_L)to peak		3°C/s max
T_s (max) to T_L -Ramp-up Rate		3°C/s max
Reflow	Temp.(T_L)(Liquidus)	217°C
	Temp.(t_L)(Liquidus)	60~150s
Peak Temp.(T_P)		260 ^{+0/-5} °C
Time within actual peak Temp.(t_p)		30s max
Ramp-down Rate		6°C/s max
Time 25°C to peak Tempe.(T_p)		8 minutes max
Do not exceed		260°C

7. Dimensions




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.059	0.071	1.500	1.800
A1	0.000	0.004	0.000	0.100
A2	0.059	0.067	1.500	1.700
b	0.026	0.030	0.650	0.750
c	0.008	0.012	0.200	0.300
D	0.252	0.260	6.400	6.600
D1	0.114	0.122	2.900	3.100
E	0.130	0.146	3.300	3.700
E1	0.270	0.281	6.850	7.150
e	0.087	0.094	2.200	2.400
e1	0.173	0.189	4.400	4.800
L	0.065	0.073	1.650	1.850
L1	0.035	0.045	0.900	1.150

Mounting PAD Layout



8. Part Marking System



9. Package Information

Package	Type	Tape Width (mm)	Quantity(pcs)
SOT-223	XN1117-ADJ	12	4000



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.