



A1UQ THRU A7UQ

1.0AMP Surface Mount General Purpose Rectifier

1. Features

- Glass passivated chip junction
- For surface mounted application.
- Low forward voltage drop.
- High current capability.
- High reliability.
- Meets MSL level 1, per J-STD-020.
- AEC-Q101 qualified available

SOD-123FL



Cathode  Anode

2. Mechanical Data

- Case: Molded plastic SOD-123FL
- Terminals: Plated leads solderable per MIL-STD-750, Method 2026 guaranteed
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- Making: Type Number

3. Maximum Ratings and Electrical Characteristics

Electrical Characteristics Rating at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	A1UQ	A2UQ	A3UQ	A4UQ	A5UQ	A6UQ	A7UQ	UNIT
	Code	A1U	A2U	A3U	A4U	A5U	A6U	A7U	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Average Rectified Output Current @T _L =100°C	I _{F(AV)}	1.0							A
Peak Forward Surge Current 8.3ms @T _j =25°C	I _{FSM}	35							A
Single half sine-wave superimposed @T _j =125°C on rated load (JEDEC Method)		28							
I ² t Rating for Fusing (t < 8.3ms)	I ² t	5.08							A ² S
Maximum Instantaneous Forward Voltage @I _F =1A	V _{FM}	1.0							V
Maximum DC reverse current @T _j =25°C	I _R	5.0							uA
at rated DC blocking voltage @T _j =125°C		100							
Typical Junction Capacitance (Note 1)	C _j	8							pF
Typical Thermal Resistance	R _{θJA}	120							°C/W
	R _{θJL}	15							
	R _{θJC}	27							
Operating Temperature Range	T _j	-55 to+150							°C
Storage Temperature Range	T _{STG}	-55 to+150							°C

Note:

1. Measured at 1.0 MHz and Applied reverse Voltage of 4.0V D.C



4. Rating And Characteristic Curves

Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Forward Surge Current Capability





Fig.4 Typical Reverse Characteristics






A1UQ THRU A7UQ


1.0AMP Surface Mount General Purpose Rectifier

5. Soldering Parameters




Reflow Condition		Lead-free
Pre Heat	Temp. min(T_s (min))	150℃
	Temp. max(T_s (min))	200℃
	Time(min to max)(t_s)	60~120s
Aver. ramp up rate(Liquidus Temp.)(T_L)to peak		3℃/s max
T_s (max) to T_L -Ramp-up Rate		3℃/s max
Reflow	Temp. (T_L)(Liquidus)	217℃
	Temp. (t_L)(Liquidus)	60~150s
Peak Temp. (T_P)		260 ^{+0/-5} ℃
Time within actual peak Temp. (t_p)		30s max
Ramp-down Rate		6℃/s max
Time 25℃ to peak Tempe. (T_P)		8 minutes max
Do not exceed		260℃

6. Dimensions




Dimensions	Inches		Millimeters	
	Min	Max	Min	Max
A	0.094	0.110	2.4	2.8
B	0.063	0.079	1.6	2.0
C	0.031	0.047	0.8	1.2
D	0.022	0.037	0.55	0.95
E	0.004	0.008	0.1	0.2
F	0.035	0.043	0.9	1.1
G	0.134	0.150	3.4	3.8

Mounting PAD Layout



7. Part Marking System



8. Package Information

Package	Tape Width (mm)	Reel Size		Quantity(pcs)	AEC-Q101	LOGO
		mm	inch			
SOD-123FL	8	178	7	3000	Yes	XN



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without from XINNUO.
- XINNUO reserves the right to make changes to this document and its products and specifications.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown her are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.